



TECHNICAL SPECS

Description:	National Flooring SPC Flooring w/ attached EVA pad.
WARRANTY:	Residential: Lifetime Commercial: 10 Year
Installation:	Floating Only Radiant Heat Approved & Below Grade Approved
Construction:	Overall Thickness 6.0mm 20 mil Wear Layer I4F TripleLock Click
Wear Finish:	2 Coats UV Cured
Dimensions:	7 1/4" (Width) x 6.0mm (Thickness) x Fixed 60" (Length)
Moldings :	94' Length



- **ACCLIMATION:** Although acclimation is NOT specifically required, **BEST INSTALLATION PRACTICE RECOMMENDS** that the product be installed close to intended occupied service temperature, generally a target of 55° F to 100° F.
- **SEASONAL HOMES:** SPC Elements is recommended for 3 season rooms and seasonal homes over concrete substrate. **Installer MUST provide at least 5/8" (16mm) expansion.**
- **PERFORMANCE TEMPERATURES:** SPC Elements is NOT recommended where the floor might experience temperature extremes beyond -30° F or greater than 155° F.
- **INSTALLATION RANGE:**
 - **Smaller Areas:** of up to 50' x 50' or total of 2500 sq. ft. must provide a 1/4" expansion gap.
 - **Larger Areas:** of up to 100' x 100' must provide a 5/8" expansion gap.