

XXTRA LONG XXTRA WIDE 100% WATERPROOF PERFORMANCE LAMINATE FLOORING

	RANDOM LENGTH 2265mm/1515mm/750mm x 235mm 12mm (underlayment required)
	Aqua Fiber Wood Based HDF
Finish:	Superior Scratch & Dent Resistance
Wear Rating:	AC4EVERPLUS
Waterproof:	100% Waterproof Performance / 72 Hour Spill Protection
Edge:	4-Sided Painted Micro Beveled
Gloss:	Low Sheen
Texture:	TruEMBOSSED Wood Grain Texture
Installation:	Floating / Uniln Click System
Warranty:	Limited Lifetime Residential
	Limited 5-Year Light Commercial

## **Product Specification Sheet**



7.5FT

LENGTH

DESCRIPTION	METHOD	RESULT	DETAILS
Class of Use	EN13329-32	Class 32	All Residential plus general commercial
Abrasion Resistance	NALFA LF-01	AC4	$IP \ge 4000 \text{ cycles}$
Impact Resistance	NALFA LF-01	Big Ball: $\geq$ 1000mm, Small Ball: $\geq$ 500mm	
Stain Resistance	NALFA LF-01	< 20	No more than slight effect
Sound Transmission	ASTM E90	drop ceiling: STC60   no drop ceiling: STC51	152mm slab
Impact Insulation Class IIC	ASTM E429	drop ceiling: IIC62   no drop ceiling: IIC52	152mm slab
Thickness Swell Test	NALFA-01	PASSED	≤ 16% (±1%)
NALFA Surface Swell Test	NALFA LF-01	< 0.5mm	Passed
Thermal Conductivity	EN14041	PASSED CLASS Cfl-S1	Suitable for Underfloor Heating System

FloorScore	Compliant	
CARB 2	Compliant	
TSCA Title VI	Compliant	floor 🐪 🦳
Content	No heavy metals + lead/cadmium present	score carb
Dangerous Substances	No carcinogenic, mutagenic or reprotoxic substances present (class 1A & 1B)	Contraction of the second s
Plasticizer	ORTHOPHTHALATES FREE	Certified By SCS Global Services
		SCS Global Services

## COLORS

ETXXL01 SHERMAN	ETXXL02 MONROE	ETXXL03 PERSHING
ETXXL04 STAGG	ETXXL05 BOOLE	ETXXL06 EUCLID
ETXXL07 NELDER	ETXXL08 ARTHUR	

Overall Thickness: 12mm (22.92 sqft/ctn 48 ctns/pallet 6pcs/ctn) RANDOM LENGTH 7.5ft + 5ft + 2.5ft Approx. Weight Per Carton: 51 lbs.



Scan the QR Code or visit www.eternityflooring.com to view our extensive line of Waterproof Performance Flooring.

## COORDINATING MOLDINGS AVAILABLE



Coordinating moldings are produced to be similar and blend as much as possible to the flooring product. Since grain patterns and the natural colors of the wood / stone patterns vary, coordinating moldings cannot be an exact match to the flooring product. Coordinating moldings do not come with warranty.

© 2022. This technical data sheet was written by Eternity Flooring Solutions. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.